


# Deimos Ultra BT A



## RANGE

CODE	NAME	DESCRIPTION
P925221 00002	DEIMOS ULTRA BT A400	Operator 24V for sliding gates up to 400kg in weight. Leaf speed 12m/min. Limit switch magnetic.
P925221 00003	DEIMOS ULTRA BT A400 V	Operator 24V for sliding gates up to 300kg in weight. Leaf speed 16m/min. Limit switch magnetic.
P925223 00002	DEIMOS ULTRA BT A600	Operator 24V for sliding gates up to 600kg in weight. Leaf speed 12m/min. Limit switch magnetic.
P925223 00003	DEIMOS ULTRA BT A600 V	Operator 24V for sliding gates up to 360kg in weight. Leaf speed 16m/min. Limit switch magnetic.



### DEIMOS ULTRA BT KIT A400 R925010 70001 / DEIMOS ULTRA BT KIT A400 V (FAST) R925011 70001

#### THE KIT INCLUDES


1 - DEIMOS ULTRA BT A400	Operator 24V for sliding gates up to 400kg in weight. Leaf speed 12m/min. Limit switch magnetic.
2 - MITTO B RCBO4 R1	12V four-channel transmitter 433MHz rolling code
4 - CP RACK	4 metres of gate rack

### DEIMOS ULTRA BT KIT A600 R925012 70001 / DEIMOS ULTRA BT KIT A600 V (FAST) R925013 70001

#### THE KIT INCLUDES

1 - DEIMOS ULTRA BT A600	Operator 24V for sliding gates up to 600kg in weight. Leaf speed 12m/min. Limit switch magnetic.
2 - MITTO B RCBO4 R1	12V four-channel transmitter 433MHz rolling code
4 - CP RACK	4 metres of gate rack

## MERAK



- Application: control unit for 1 24V operator for sliding gates
- Board power supply: 230V single-phase
- Operator power supply: 24V 80W
- Main characteristics: removable terminal boards with the new colour standard, simplified programming with scenario display, integrated two-channel receiver, D-Track based antisquashing system and slowdown during opening or closing.
- Main functions: automatic closing, quick closing, pedestrian passage, people-present operation, maintenance warnings.
- Compatibility: HQSC-D, QSC-D MA



tuned to you

# Deimos Ultra BT A




## TECHNICAL SPECIFICATIONS

DEIMOS ULTRA BT A400 DEIMOS ULTRA BT A600

Control unit	MERAK SL1	MERAK SL2
Power supply	24V	24V
Power input	50W	70W
Type of limit switch	magnetic	magnetic
Pinion module	4	4
Slowdown	yes	yes
Ecosol	yes	yes
Impact reaction	d-track	d-track
Locking	mechanical	mechanical
Release	lever-operated with personal key	lever-operated with personal key
Frequency of use	intensive	intensive
Environmental conditions	from -20°C to 55°C	
Actuator weight	7kg	8kg

## DIMENSIONS



## ACCESSORIES




### CP - D221073

Plastic rack, 4-module, cross-section 22 x 22 mm, length 1 m, screw-fitted into slots



### RB - P121016

4-channel wall-mounted radio control with rolling code



### CVZ - D571053

Steel rack, 4-module, cross-section 30 x 12 mm, length 1 m, screw-fitted on supports (supplied)



### CELLULA 130

Pair of self-aligning photocells for external application (range 30 m) Power supply 24V ac/dc



### B EBA 201 R01 - P111468

Expansion board for connection of central units with serial controls management



### THEA A15 - P111526

Pair of self-aligning photocells for external application (range 30m) Power supply 24V ac/dc



### Q.BO TOUCH - P121024

Wireless digital keypad 433 MHz Rolling code



### AKTA A30 - P111536

Pair of orientable photocells (180°horiz./20°vert.). For external application (range 30m) 24V ac/dc



### AEL 433 - D113632

Antenna for 433 Mhz radio remote control with 4 m cable



### ERIS A30 - P111537

Pair of wireless photocells with the possibility of managing an active infrared or resistive sensitive edge



### MITTO BRCBO 4 R1

12 v four channel transmitter 433MHZ rolling code. Blue transmitters supplied in kits. Other colours available.



### SL BAT1 - P125033

SL BAT1 emergency battery kit for DEIMOS ULTRA BT



tuned to you