## **ACCESSORIES**



## Control device



**D113084 - PC 2E**Key switch for exterior with metal case. [10 pcs/package].



**P121011 - INTRO**Key switch for exteriors.
Flush and column version.



P121014 - SC NET Key switch SC NET.



**D531097 - CRC**Spare coded key for [10 pcs/package]. When ordering, specify key series number.



P111001 00003 - RMM 2 Two-channel metal detectors. 230V~



**D121012 - CM**Magnetic key for LCM readers (10 pcs/package).



**D731022 - CLC**Column for magnetic key readers. Height 1 m.



**D121011 - LCM**Magnetic key reader. For column mounting - see model CLC.



**D121458 - PARKY LIGHT** Traffic light



P111274 - RME

Single-channel metal detector with installation base. Power supply 24Vac. Power supply LED. Channel LED. Pulse on release configuration. Presence relay with pulse or continuous operation. Pulse relay with deactivation possibility.



**D110926 00001 - SPIRA 2X1** Magnetic loop 2x1 m.



**D121009 - PE2**External two-button panel [10 pcs/package].



P121012 - SELETTO

Flush digital pushbutton panel, programmable for controlling pedestrian and vehicle access, usable with two operating modes: with "serial connection" and with "interfacing with the COMPASS system"



P121013 - SELETTO E

Flush digital ext. pushbutton panel, programmable for controlling pedestrian and vehicle access, usable with two operating modes: with serial connection and with interfacing with the COMPASS system.



P123001 00001 - EBP

230 Vac electric lock with zero stop resistance. Also available in 50 mm, 75 mm versions and at 24V.

## **ACCESSORIES**





P123006 00001 - EBPE 52 230Vac electric lock with zero stop resistance, with external release for max 50mm thick doors and gates



P123008 00001 - EBPE 75 230Vac electric lock with zero stop resistance, with external release for max 75mm thick doors and gates.



P123001 00013 - EBP 24 24Vac electric lock with 230/24V transformer to be inserted in the control panel



**D121016 - ECB DX** RH horizontal electric lock, 12V.



D121017 - ECB SX
Left-hand horizontal electric lock, 12 V. lock.

For system composition and installation refer to the regulations in force in the country where the system is being installed. The indicated data are not binding. BFT reserves the right to make modifications without prior notice.